

Amendments to the Claims

This listing of claims will replace all prior versions and listings of claims in the Application.

1. (Original) A device for anchoring a suture used in a surgical procedure to a coiled helical member, comprising winding means for winding a suture around the helical member in a helical path such that the suture is attached to at least one turn of the helical member.

2. (Currently Amended) A device in accordance with Claim 1, further comprising a casing, said winding means being ~~rotatable~~ rotatably mounted to said casing.

3. (Original) A device in accordance with Claim 2, wherein said casing is sized and shaped so as to be gripped by a hand of a surgeon.

4. (Original) A device in accordance with Claim 3, wherein said winding means includes a winding tube rotatable about an axis, said winding tube being movable in an axial direction in response to its rotational movement.

5. (Original) A device in accordance with Claim 4, wherein said winding tube includes securing means for securing at least one portion of the suture thereto so as to cause the suture to wind about the helical member.

6. (Original) A device in accordance with Claim 5, wherein said securing means includes a groove formed in said winding tube and sized and shaped so as to receive at least one portion of the suture therein.

7. (Currently Amended) A device in accordance with Claim 6, wherein said groove is angled in a direction ~~substantially~~ opposite to the direction of rotation of said winding tube during the winding of the suture about the helical member.

8. (Original) A device in accordance with Claim 7, wherein said winding tube includes a plurality of first screw threads formed thereon, said casing including a plurality of second screw threads mating with said first screw threads such that said winding tube is movable in said axial direction in response to its rotational movement.

~~40.~~ 9 (Currently Amended) A device in accordance with Claim ~~9~~ 8, wherein said winding tube includes a first gear mounted thereon, said casing including a first actuator movably mounted on said casing and adapted for manual actuation by a surgeon, said casing including a set of second gears, said first gear being engaged with one of said second gears, said first actuator being engaged with another of said second gears such that said first gear and hence said winding tube are rotatable in response to the movement of said first actuator.

~~44.~~ 10. (Currently Amended) A device in accordance with Claim ~~40~~ 9, further comprising supporting means for supporting the helical member during the winding of the suture around the helical member.

~~42.~~ 11. (Currently Amended) A device in accordance with Claim ~~44~~ 10, wherein said supporting means includes a guide tube rotatably mounted in said winding tube.

~~43.~~ 12. (Currently Amended) A device in accordance with Claim ~~42~~ 11, wherein said guide tube includes a coiled spiral member at an end thereof, said spiral member being sized and shaped so as to receive the helical member therein during the winding of the suture about the helical member.

~~44.~~ 13. (Currently Amended) A device in accordance with Claim ~~43~~ 12, wherein said guide tube is movable in said axial direction relative to said winding tube in response to the rotation of said guide tube.

~~45.~~ 14. (Currently Amended) A device in accordance with Claim ~~44~~ 13, wherein said guide tube has an opening extending through said spiral member, said opening being sized and shaped so as to receive the helical member therein.

~~46.~~ 15. (Currently Amended) A device in accordance with Claim ~~45~~ 14, wherein said spiral member includes a plurality of lobes extending radially inwardly into said opening, said lobes forming a plurality of spaces positioned radially outwardly from said opening.

~~47.~~ 16. (Currently Amended) A device in accordance with Claim ~~46~~ 15, wherein said guide tube includes a plurality of third screw threads formed thereon, said casing including a plurality of fourth screw threads mating with said third screw threads such that said guide tube is movable in said axial direction in response to the rotational movement of said guide tube.

~~48.~~ 17. (Currently Amended) A device in accordance with Claim ~~47~~ 16, wherein said guide tube includes a third gear mounted thereon, said casing including a second actuator movably mounted on said casing and adapted for manual actuation by a surgeon, said casing including a set of fourth gears, said third gear being engaged with one of said fourth gears, said second actuator being engaged with another of said fourth gears such that said third gear and hence said guide tube are rotatable in response to the movement of said second actuator.

~~49.~~ 18. (Currently Amended) A device in accordance with Claim ~~48~~ 17, further comprising a support rod extending through said guide tube for positioning the helical member in said opening of said spiral member of said guide tube.

~~20.~~ 19. (Currently Amended) A device in accordance with Claim ~~49~~ 18, wherein said support rod includes a distal end sized and shaped so as to engage the helical member:

~~24.~~ 20. (Currently Amended) A device in accordance with Claim ~~20~~ 19, wherein said distal end of said support rod is sized and shaped so as to engage the helical

member by a friction fit.

~~22.~~ 21. (Currently Amended) A device in accordance with Claim ~~20~~ 19, wherein said support rod is sized and shaped so as to support additional coiled helical members thereon.

~~23.~~ 22. (Currently Amended) A device in accordance with Claim ~~22~~ 21, further comprising advancing means for advancing the additional helical members forward in said axial direction.

~~24.~~ 23. (Currently Amended) A device in accordance with Claim ~~23~~ 22, wherein said advancing means includes a plunger mounted on said support rod, said plunger being movable in said axial direction.

~~25.~~ 24. (Currently Amended) A device in accordance with Claim ~~1~~, wherein said winding means includes a winding tube rotatable about an axis, said winding tube being movable in an axial direction in response to its rotational movement.

~~26.~~ 25. (Currently Amended) A device in accordance with Claim ~~25~~ 24, wherein said winding tube includes securing means for securing at least one portion of the suture thereto so as to cause the suture to wind about the helical member.

~~27.~~ 26. (Currently Amended) A device in accordance with Claim ~~26~~ 25, wherein said securing means includes a groove formed in said winding tube sized and

shaped so as to receive at least one portion of the suture therein, said groove being angled in a direction substantially opposite to the direction of rotation of said winding tube during the winding of the suture about the helical member.

~~28.~~ 27. (Currently Amended) A device in accordance with Claim 1, further comprising supporting means for supporting the helical member during the winding of the suture around the helical member.

~~29.~~ 28. (Currently Amended) A device in accordance with Claim ~~28~~ 27, wherein said supporting means includes a guide tube rotatably mounted in said winding means, said guide tube including a coiled spiral member at an end thereof, said spiral member being sized and shaped so as to receive the helical member therein during the winding of the suture about the helical member.

~~30.~~ 29. (Currently Amended) A device in accordance with Claim ~~29~~ 28, wherein said guide tube is movable in an axial direction relative to said winding means in response to the rotation of said guide tube.

~~34.~~ 30. (Currently Amended) A device in accordance with Claim 1, further comprising a support rod extending through said winding means for supporting the helical member relative to said winding means.

~~32.~~ 31. (Currently Amended) A device in accordance with Claim ~~34~~ 30, wherein said support rod includes a distal end sized and shaped so as to engage the

helical member by a friction fit.

~~33.~~ 32. (Currently Amended) A device in accordance with Claim ~~34~~ 30, wherein said support rod includes a distal end sized and shaped so as to engage the helical member, said support rod being sized and shaped so as to support additional coiled helical members thereon.

~~34.~~ 33. (Currently Amended) A device for anchoring a cord to a coiled helical member, said device comprising winding means for winding a cord around the helical member in a helical path such that the cord is attached to at least one turn of the helical member.

~~35.~~ 34. (Currently Amended) A device in accordance with Claim ~~34~~ 33, wherein said winding means includes a winding tube rotatable about an axis, said winding tube movable in an axial direction in response to its rotational movement.

~~36.~~ 35. (Currently Amended) A device in accordance with Claim ~~35~~ 34, wherein said winding tube includes securing means for securing at least one portion of the suture cord thereto so as to cause the suture cord to wind about the helical member, said securing means including a groove formed in said winding tube sized and shaped so as to receive at least one portion of the suture cord therein, said groove being angled in a direction substantially opposite to the direction of rotation of said winding tube during the winding of the suture cord about the helical member.

~~37.~~ 36. (Currently Amended) A device in accordance with Claim ~~36~~ 35, further comprising a guide tube for supporting the helical member during the winding of the ~~suture cord~~ around the helical member, said guide tube being rotatably mounted in said winding tube, said guide tube including a coiled spiral member at an end thereof, said spiral member being sized and shaped so as to receive the helical member therein during the winding of the ~~suture cord~~ about the helical member.

~~38.~~ 37. (Currently Amended) A device in accordance with Claim ~~37~~ 36, wherein said guide tube is movable in said axial direction relative to said winding tube in response to the rotation of said guide tube.

~~39.~~ 38. (Currently Amended) A device in accordance with Claim ~~38~~ 37, further comprising a support rod extending through said guide tube for positioning the helical member in said spiral member of said guide tube.

~~40.~~ 39. (Currently Amended) A method of anchoring a suture used in a surgical procedure to a coiled helical member, comprising the steps of supporting the helical member relative to a winding tube; and moving said winding tube relative to the helical member such that the suture is wound about the helical member in a helical path so as to attach the suture to at least one turn of the helical member.

~~41.~~ 40. (Currently Amended) A method in accordance with Claim ~~40~~ 39, wherein said winding tube is rotatable about an axis, said winding tube being movable in an axial direction in response to its rotational movement.

~~42.~~ 41. (Currently Amended) A method in accordance with Claim ~~44~~ 40, wherein said supporting step includes the step of positioning the helical member in a coiled spiral member of a guide tube.